



VersaTech 1100 ULB

Bariatric Ultra-Low Bed



Technical specifications

Platform width:	Adjustable from 35" to 38" to 41" to 47" to 53" (89 cm to 97 cm to 104 cm to 119 cm to 134 cm)	Maximum height:	32" (81 cm)
Overall width at 35":	40" (101 cm)	Load capacity:	1100 lb (499 kg)
Overall width at 53":	57" (144 cm)	Backrest angle:	70°
Platform length:	80" to 84" to 88" (203 cm to 213 cm to 223 cm)	Footrest angle:	34°
Overall length at 80":	93 1/8" (237 cm)	Trendelenburg position:	-14° to +14° (degrees)
Overall length at 88":	101 1/8" (257 cm)	Under bed clearance:	5 7/8" (14,9 cm)
Minimum height:	8" (21 cm)	Bed weight:	438 lb (199 kg)

VersaTech 1100 ULB

Features

- Easily expandable in width (press buttons) that can accommodate mattresses of 36", 39", 42" 48" and even 54"
- Load capacity of 1100 lb (499 kg) for bariatric use
- Prevent Falls Related Injuries: 8" (21 cm) Ultra-Low Bed
- Ultra quiet DC motors. Helps maintain a calm and relaxed environment
- Emergency battery for temporary autonomy
- Easy to maintain with quick connect components
- Central brake: one pedal at the foot of the bed
- Lightweight composite head and footboard for ease of use.
- Antimicrobial and easy to clean powder coated steel structure
- 5" (125mm) anti-static double wheels casters
- 2 pairs of half-length composite siderails
- Patient remote control with auto-contour
- Patient control integrated into the bed siderails with auto-contour, underbed light and nurse call
- Nurse call built into the siderails with DB-37 connexion
- Easy to use nurse control integrated in the footboard
- Bed functions lock-out from the nurse control at the footboard
- Side and foot mattress retainer
- Backrest angle indicator
- Easily extendable in length without tools from 80" to 84" to 88" (203 cm to 213 cm to 223 cm)
- One-touch Trendelenburg adjustment
- Night light
- Multiple openings for restraint straps
- Bumpers at the head of the bed
- IV pole holders
- Trapeze bar receptacle
- Electric CPR
- Mechanical CPR: 2 handles
- Authentic Canadian product
- CSA certified according to Canadian and American standards.

Options

- Integrated scale with 2 zones bed exit notification, integrated warning signal to DB-37 port with visual and audible indicator

Accessories

- Bar with trapeze
- IV pole
- Left retractable IV pole
- Right retractable IV pole
- Support for oxygen cylinder
- Pump support
- DB-37 adapter cable
- Additional remote control
- Bed trolley
- Siderail protectors
- Mattress length extension 4"
- Mattress V1100 with 3 width extension

Electronic

- Voltage: 120 V AC
- Amperage: 4 A
- Frequency: 60Hz
- Leakage current: <300 microamps
- Battery: 1.2aH sealed lead acid, 2 x 12V
- Scale accuracy (regardless of the bed position): 1% of the patient weight

